S Seakeeper	QUICK START GUIDE	Product:	Document #:	Rev:	Page:
		SEAKEEPER CONNECTBOX AND APPLICATION QUICK START GUIDE	90569	2	1 of 2

The Seakeeper can be controlled from either the ConnectBox or the Seakeeper Application on the Seakeeper 5" Touch Display and/or a compatible MFD.

USING THE CONNECTBOX

START-UP

- 1) Energize Seakeeper power supply.
- 2) When the power is turned on, the ConnectBox will initialize and the POWER button will pulsate.



STABILIZATION

For stabilization at sea or at anchor after the Seakeeper is above the Stabilization RPM:



SHUT-DOWN

The Seakeeper should be stopped when stabilization is no longer required. Once the vessel is secured at a berth or mooring, switch the DC power to the Seakeeper off. The flywheel will continue to decelerate to 0 RPM.





USING THE SEAKEEPER APPLICATION

START-UP

- 1) Energize the Seakeeper power supply.
- 2) When the power is turned on, the Application will initialize, and the Home Screen will appear.



STABILIZATION

For stabilization at sea or at anchor after the Seakeeper is above the Stabilization RPM:



Press the STABILIZE button. The button will turn blue, indicating that the Seakeeper is stabilizing the roll motion.

SHUT-DOWN

The Seakeeper should be stopped when stabilization is no longer required. Once the vessel is secured, at a berth or mooring, switch the DC power to the Seakeeper off. The flywheel will decelerate to 0 RPM.

	MOTOR SPEED: 0 RPM SEAKEEPER ANGLE: 0.0° CURRENT: 0.0 A ENCLOSURE: 0 Torr BATTERY: 12.0V DRIVE: 32.0° F		
Press POWER button. The button will turn grey.	When the Seakeeper is turned off, the flywheel is still spinning. When the flywheel has come to a complete stop, 0 RPM will appear on the service screen indicating that the flywheel has stopped. It may take 2+ hours to reach 0 RPM. Please refer to the Operation Manual for your Seakeeper model.		