
NOTE:


8

1) THESE COMPONENTS ARE TO BE USED DURING A THRU-BOLT INSTALLATION OF SEAKEEPER 2 TO ANY METAL OR FIBERGLASS SURFACE STRUCTURE IN ACCORDANCE TO THE SEAKEEPER 2 GENERIC INSTALLATION GUIDE. THE 4 GASKET PADS MUST BE USED BETWEEN THE ALUMINUM GYRO FRAME AND ANY DISSIMILAR METAL STRUCTURE THAT THE GYRO WILL BOLT AGAINST. THE BOLTS SUPPLIED ARE CLASS 10.9 ZINC-NICKEL PLATED ALLOY STEEL, M14-2.0 X 100mm LG. ANY OTHER LENGTH NEEDED MUST BE SUPPLIED BY INSTALLER. SEAKEEPER RECOMMENDS THE USE OF A MODERATE COAT OF MARINE ANTI-SEIZE (E.G., SAF-T-EZE NICKEL GRADE ANTI-SEIZE, SBT-4N OR EQUIVALENT) TO THE THREADS OF EACH BOLT. SEAKEEPER ALSO RECOMMENDS USING A MARINE GRADE SEALANT (E.G., SILI-THANE 803 OR EQUIVALENT) UNDER EACH BOLT HEAD AND WASHER TO HELP PREVENT CORROSION OF BOLTS.


## PACKAGING INSTRUCTIONS:

- a) PACKAGE EACH PART NUMBER ITEM IN A BAG AND LABEL EACH BAG WITH PART NUMBER.
- b) PLACE A COPY OF 90492, SEAKEEPER 2 BOLT-IN CLEARANCES, INSIDE THE PACKAGING.
- c) LABEL THE ENTIRE KIT "90636 SEAKEEPER 2 THRU-BOLT KIT".






--- INITIAL RELEASE



REV NO. ECN NO. ZONE

0906



DATE


07/28/2021

APPRVD.

TMD

2

**DESCRIPTION** 



5	90492	SK2 BOLT-IN CLEARANCES	1	
4	60809	M14-2.0, EXTRA WIDE HEX, 2H, HEAVY NUT	4	
3	60808	SCREW, HEX HD CAP, M14-2.0 X 100MM LG, PART TD, GRD 10.9, Zn-Ni PLTD STEEL	4	
2	60532	WASHER, WEDGE LOCK M14, .60ID X 1.21 OD, DELTA PROTEKT PLTD STEEL	8	
1	11840	SEAKEEPER 2 FOUNDATION ISOLATION GASKET	4	
ITEM NO.	PART NO.	DESCRIPTION	QTY.	NOTE

	PROPRIETARY A	AND CONFIDENTIAL	
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEAKEEPER INCORPORATED. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEAKEEPER IS PROHIBITED.		Seake
VEIGHT - LBS :			NAME:
I (I LI (I) (L.	DRAWN: TMD	DATE: 08MAR2021	
	ENG APPR:  DMF PROD APPR:	DATE: 26MAR2021	DWG NU



SEAKEEPER 2 THRU-BOLT KIT

WG NUMBER REV. NO. SHEET NO. 1 OF 1

7 6 5 4 3