8	7	6	5	4					
NOTE:									
	1) THESE COMPONENTS ARE TO BE USED DURING A DIRECT BOLT-IN INSTALLATION OF								
SEAKEEPER 5/6 TO ANY METAI	SEAKEEPER 5/6 TO ANY METAL OR FIBERGLASS SURFACE STRUCTURE IN ACCORDANCE TO								
THE SEAKEEPER 5/6 GENERIC INSTALLATION GUIDE. THE 4 GASKET PADS MUST BE USED									
BETWEEN THE ALUMINUM GY	BETWEEN THE ALUMINUM GYRO FRAME SPACERS AND ANY DISSIMILAR METAL STRUCTURE THAT THE								
GYRO WILL BOLT AGAINST. TH	GYRO WILL BOLT AGAINST. THE BOLTS SUPPLIED ARE CLASS 10.9 ZINC-NICKEL PLATED								

ALLOY STEEL, M12-1.75 X 80mm LG. ANY OTHER LENGTH NEEDED MUST BE SUPPLIED BY INSTALLER. SEAKEEPER RECOMMENDS THE USE OF A MODERATE COAT OF MARINE ANTI-SEIZE (E.G., SAF-T-EZE NICKEL GRADE ANTI-SEIZE, SBT-4N OR EQUIVALENT) TO THE THREADS OF EACH BOLT. SEAKEEPER ALSO RECOMMENDS USING A MARINE GRADE SEALANT (E.G., SILI-THANE 803 OR EQUIVALENT) UNDER EACH BOLT HEAD AND WASHER TO HELP PREVENT CORROSION OF BOLTS.

PACKAGING INSTRUCTIONS:

F

Е

D

С


А


8

a) PACKAGE EACH PART NUMBER ITEM IN A BAG AND LABEL EACH BAG WITH PART NUMBER.b) PLACE A COPY OF THE SEAKEEPER 5/6 BOLT-IN CLEARANCES, ITEM #5, INSIDE THE PACKAGING.

<u>/4.1</u>

c) LABEL THE ENTIRE KIT "90400, SEAKEEPER 6 BLIND-HOLE KIT".





6

7

5	90391	SEAI
4	60846	SCR
3	60844	WAS
2	11241	SEAI
1	11145	SEAI
ITEM NO.	PART NO.	

5


		3	2		1	
REV NO.	ECN NO.	ZONE	DESCRIPTION	DATE	DRAWN	APPRVD.
2	-		REPLACED 60428 WITH 60482	14FEB2019		BRD
3	765		SK5 RELAUNCH	28JUN2019		AVM
4	908	E5	RE-DRAWN, RPL: 60387 W/ 60846, 60482 AND 60252 W/ 60844	3AUG2021		ZGY
4.1	1059	E7	DESCRIPTION CHANGE FROM "BOLT-IN" TO "BLIND HOLE".	4APR2023	RMF	

Е

D

С

В



SEAKEEPER 5-6 BOLT-IN CLEARANCES							
SCREW, HEX HD CAP, M12-1.75 X 80M	Zn-	Zn-Ni PLTD STL					
WASHER, WEDGE LOCK, .511D X .77 OD (STANDARD OD), DELTA PROTEKT PLTD STL					ROTEKT PLTD STL	16	
SEAKEEPER 6 FOUNDATION SPACER					61-T6 (SS)	4	
SEAKEEPER 6 FRAME ISOLATION GASKE	.063 THK	GAROLITE G10	4				
DES	N	QTY.					
	PROPRIETARY AND C THE INFORMATION C THIS DRAWING IS THE OF SEAKEEPER INCOR REPRODUCTION IN WHOLE WITHOUT PERMISSION OF SI PROHIBIT THIS DRAWING S ALL OTHER FILE FC UNLESS OTHERWIS DO NOT SCALE	CONTAINED IN SOLE PROPERTY RPORATED. ANY PART OR AS A THE WRITTEN EAKEEPER IS ED. UPERSEDES DRMAT TYPES SE SPECIFIED	WEIGHT - LBS : D MATERIAL: 	Seakeeper Inc. 4531 ESCRIPTION: SEAKEEI	KEEPER 5/6 BLIND-HOLE KI		
4 3			2		1		