NOTES: 1) MANIFOLD IS PROVIDED TO SEAKEEPER AS A COMPLETE, TESTED ASSEMBLY WITHOUT GLYCOL COOLANT.
- MANIFOLD IS PROVIDED TO SEAKEEPER WITH ATOS VALVE INSTALLED BY BUCHER.

2) THE MANIFOLD BLOCK IS CUSTOM MACHINED, DE-BURRED, CLEANED AND PRESSURE TESTED BY VENDOR.

3) MANIFOLD BLOCK FINISH: STANDARD BLACK HARD COAT.

4) ALL EXTERIOR COMPONENTS TO BE ZINC-NICKEL PLATED FOR 750+ SALT SPRAY LIFE.

5) ALL OPEN PORTS AND ELECTRICAL CONNECTIONS SHALL HAVE PROTECTIVE PLUGS OR CAPS INSTALLED PRIOR TO SHIPMENT.

6) FALLING PRESSURE SETPOINT 165 PSI ± 15 PSI (INTENDED SYSTEM CHARGE PRESSURE 350 PSI).

7) REPLACEMENT COIL FOR ITEM 8, PROPORTIONAL VALVE: ATOS PART# COZEK-6DC / SEAKEEPER #50258.

8) REPLACEMENT COIL FOR ITEM 6, SOLENOID: BUCHER HYDRAULICS PART# 400280152 / SEAKEEPER #50342.

20-25 FT-LBS 7	ATOS DO3 VALVE (SEAKEEPER PART # 50313) SHOWN FOR REFERENCE. SEE DWG # 11676.
4X	
40 FT-LBS 12 4X	
41	2 12-15 FT-LBS NOTE 11
9	(5) 35-40 FT-LBS
12-15 FT-LBS NOTE 11	NOTE: SEAKEEPER PART# 50294, ACCUMULATOR, 1 L, SAE -08 PORT (NOT SHOWN) TO BE INSTALLED BY SEAKEEPER. SEE DWG # 11676.
26-32 FT-LB	S

	6	(13)	26-32 FT-LBS	
15-20 FT-LBS		15-20 FT-LBS	(6)	
3			25-30 FT-LBS	
				40-45 FT-LBS
				4 4X
5-7 FT-LBS				
14		00		
4X		(B) 23		

REV NO.	ECN NO.	ZONE	DESCRIPTION	DATE	APPRVD.
2	0827		REMOVED ADAPTOR PLATE, 50290ADPT; RELOCATED THE ACCUMULATOR PORT; CORRECTED THE ACCUMULATOR FITTING; (4X) SHCS LENGTH CHANGED FROM 1.75IN (#92196A252) TO 1.25IN (#92196A249) AND BUCHER DWG. #520-9-004470 CHANGED FROM REV C TO REV D	5/15/2020	WMG
3	0876		REPLACED INCORRECT PART# 50239 WITH 50278 ADAPTOR FITTING; SINCE WE REMOVED THE ADAPTOR PLATE, 50290ADPT, THE PLUG, MORB, SAE-02 AND 0-RING, SIZE 012, 1/16" WD, DUROMETER 90 NO LONGER NEEDED	2/24/2021	TMD
4	1102		CHANGED SWITCH SETPOINT, WAS 150 PSI. ADDED NOTE 13. CHANGED BUCHER DWG REV. ADDED WEIGHT.	10/17/2023	AMP
5	1102		REMOVED PART MARK NOTE. CHANGED PRESSURE SWITCH P/N, WAS 50343.	04DEC2023	AMP

PORT SCHEDULE				
NAME	SIZE	ITEM NO.		
C1	NPTF 06	2	Е	
C2	NPTF 06	1		
CHG	SAE #4	3		
ACC	SAE #8	5		
PS	SAE #4	14		
UT	SAE #8	4		
LR	SAE #8	4		
UR	SAE #8	4		
LT	SAE #8	4		
2.1	SAE #8	7, 13		
2.2	SAE #8	7, 13		
2.3	SAE #8	7, 13		
2.4	SAE #8	7, 13		
3.1	SAE #8	9)	
8.1	SAE #8	6	ט	
8.2	SAE #8	6		

	14		SCREW, SOCKET HD, 10-24 X 1.25"	18-8 SS	4		
5	13	50408	PRESSURE SWITCH, 165 PSI	ZnNi PLTD	1	NOTE 6	
	12	50341	PLUG, SKT HEX, SAE ORB -08, ZN-NI PLATED	ZINC NICKEL PLATED STEEL	4		С
	11	50340	PLUG, SKT HEX, SAE ORB -06, ZN-NI PLATED	ZINC NICKEL PLATED STEEL	5	TORQUE TO 35 FT-LBS	
	10	50339	PLUG, SKT HEX, SAE ORB -04	ZINC NICKEL PLATED STEEL	12	TORQUE TO 10 FT-LBS	
	9	50338	SK6 RECTIFIED MANIFOLD BLOCK	AL 6061-T6, ANODIZED	1	NOTE 3	
	8	50335	FLOW CONTROL NEEDLE	ZnNi PLTD	1	SEAL KIT P/N: 5207300005	
	7	50292	CHECK VALVE, SIZE 08, 0.2 BAR		4	INSTALLED IN MANIFOLD	
	6	50291	2 WAY SOLENOID BLOCKING VALVE W/ REVERSE FLOW CHECK, 12VDC	ZnNi PLTD	2	NOTE 8	В
	5	50278	ADAPTOR FITTING, -08 MORB X -08 MORB UNION	ZINC NICKEL PLTD	1		
	4	50226	ADAPTOR, -08 SAEORB TO -08 JIC MALE STRAIGHT, ZN-NI PLATED	ZINC NICKEL PLTD	4		
	3	50006	TEST PORT FITTING W/ PLASTIC CAP	STEEL/PLASTIC	1		
	2	40298	ELBOW, 90 DEG BARBED FTG. 1/2" HOSE ID X 3/8" NPT MALE	BRASS	1	NOTE 11	
	1	40257	ELBOW, 45 DEG BARBED FTG 1/2" HOSE ID X 3/8" NPT MALE	BRASS	1	NOTE 11	
	ITEM NO.	PART NO.	DESCRIPTION	MATERIAL	QTY.	NOTE	

THIS DRAWING IS THE SOLE PROPERTY THIS DRAWING IS THE SOLE FROM LINE OF SEAKEEPER INCORPORATED. ANY WEIGHT - LBS: REPRODUCTION IN PART OR AS A
WHOLE WITHOUT THE WRITTEN
PERMISSION OF SEAKEEPER IS MATERIAL: PROHIBITED. THIS DRAWING SUPERSEDES ALL OTHER FILE FORMAT TYPES UNLESS OTHERWISE SPECIFIED

THE INFORMATION CONTAINED IN

DO NOT SCALE DRAWING

PROPRIETARY AND CONFIDENTIAL 3rd ANGLE PROJECTION SEAKEEPER Seakeeper Inc. 45310 Abell House Lane, Suite 350 California, MD 20619

DESCRIPTION: 17.5 SEAKEEPER 6 RECTIFIED MANIFOLD

ASSEMBLY, D03 VALVE, BUCHER REV NO: SCALE: SHEET NO: DRAWING NO: 50290-SP 5 1:2 | 1 OF 1

2